

ADVENTURE ON Water



OUTBOARD ENGINES

Honda Motor Europe Ltd

Cain Road, Bracknell, Berkshire, RG12 1HL United Kingdom Honda Contract Centre 0345 200 8000 w.honda.co.uk

tion details do not apply to any part The manufacturer reserves the right to vary their specific with or without notice at such times in such manner as



BRINGING THE BEST ENGINE INNOVATION TO THE WATER

ONDA

50

VB

As the largest engine manufacturer in the world, we know quite a lot about how to make a great engine for any purpose. In fact, over two thirds of the 5 million engines we make every year are for our competitors and other manufacturers, so they obviously think so too. Our engines are trusted by millions of users everyday, all over the world, for countless tasks and applications. With over 50 years of innovation, testing, refining and testing again, we know what makes a great engine, and we inject all of that knowledge into our outboard range.

CONTENTS

- 03 Why Honda?
- 05 Honda Marine Innovation
- 07 BF350/BF300
- 09 BF250/BF225/BF200/BF175
- 11 BF150/BF135/BF115/BF100/BF80
- 13 BFP60/BF60/BF50/BF40
- 15 BF30/BF20/BF15/BF10/BF8
- 17 BF6/BF5/BF4/BF2.3
- 19 Honwave
- 21 Accessories and Rigging



ANT A Store

130MDA













THE POWER YOU NEED, FOR THE LIFESTYLE YOU WANT

FOR THE MOMENTS

HOND

There's an incredible depth of feeling that flows through every person who owns, and works with a boat. This joy, this relentless, overwhelming passion for a life on the water, fuels everything we do and every product we create.

FOR THE ADVENTURES

There's nothing like the freedom to choose your own course. With engines designed and built for everyone's needs, embrace every adventure, every trip and every Saturday afternoon jaunt, without a drop of hesitation.

FOR LIFE

We make the most reliable and trustworthy engines in the world. It sounds impressive, but what it really means is that we're there when it matters. And when it matters, people choose Honda, time and time again.

HONDA MARINE INNOVATION

At Honda, we have always been passionate about new technology. By constantly pushing the boundaries of what is possible, we are able to give you more. More performance, more fuel efficiency, more control. Take a look at our latest innovations to see how you can get the most out of your outboard engine.





EVERY ENGINE FOR ANY ADVENTURE

From 2.3 HP to the all-new V8 BF350 you'll find the perfect outboard motor to match the power, performance, and practicality you need. Seek out your sweet spot between the advanced technology features, ease of use, optimal fuel efficiency, horsepower and price.

PERFORMANCE

▼TEC™ - VARIABLE VALVE TIMING AND LIFT ELECTRONIC CONTROL Optimises engine performance throughout engine rpm range PGM-FI - PROGRAMMED PGM-FI FUEL INJECTION

PGM-FI controls full optimisation of your engine performance and reliability

ЕСОто ECOmo

Superior fuel efficiency

EASE OF USE

HONDA iST പ്ര

Intelligent shift and throttle for smooth throttle and gear shifting

<u>۲</u> MULTI-FUNCTION TILLER HANDLE 699

Adjustable tiller handle for maximum comfort with conveniently located controls

Ja R

RECOIL START Simplified and compact for easy starting

COUNTER ROTATING GEARBOX Improves boat handling for reduced steering effort

N M E A 2 O O O ®

Simplified connectivity for compliance with other NMEA2000[®] electronic equipment



Automatically operates trim according to engine or boat speed

CRUISE CONTROL Adjust boat speed with a press of a button

PORTABILITY



Compact, lightweight design for easy portability

INTEGRATED FUEL TANK 5

Enhanced portability and convenience



INTEGRATED CARRYING HANDLE Enhances portability

 $\widetilde{\mathbf{d}}$

ଂମ୍ପି

لركور

PAST

BLAST[™] - BOOSTED LOW SPEED TORQUE

Excellent holeshot performance

PGM-IG

PGM-IG - HONDA PROGRAMMED IGNITION

Honda Programmed Ignition accurately controls ignition timing for optimum overall operation

POWER INTAKE AIR SYSTEM

Unique system providing increased engine power and superior cooling



(17)

MECHANICAL CONTROL Ergonomic and responsive remote control

POWER TRIM AND TILT Electric engine trim and tilt optimises performance

ELECTRIC START Effortless and easy starting

ENGINE PROTECTION AND SECURITY Engine monitoring function

THROUGH HUB EXHAUST Provides increased thrust and reduced operating noise

AUTOMATIC TILT Preset easy tilt operation when stored or mooring



TROLLING CONTROL MODE

Giving accurate slow speed control



360° STEERING 360° steering for simplified manoeuvrability



THROTTLE TENSIONER Refines steering throttle control



BF350/BF300

07

THE V8 RANGE. REDEFINING HIGH-PERFORMANCE OUTBOARD ENGINES

Now you can have it all on the water – ultimate comfort combined with high-powered performance. Our V8 range offers technically advanced outboard engines allowing you to explore further, experience more, and take your time on the water to whole new levels. Enjoy the precision of rapid acceleration, the reassurance of intelligent fuel efficiency and, most importantly, the backing of years of proven Honda engineering.

PERFECT FOR LONGER, COMFORTABLE ADVENTURES AND EFFORTLESS LEISURE

FUEL CONSUMPTION

Engine speed (rpm)	Speed (knots)	Consumption (l/h)	MPL
650	2,8	5,2	0,54
1.000	5,0	9,6	0,52
1.500	7,3	19,4	0,38
2.000	9,0	33,3	0,27
2.500	16,2	48,4	0,33
3.000	24,6	53,4	0,46
3.500	30,8	68,1	0,45
4.000	36,2	102,2	0,35
4.500	40,3	124,0	0,33
5.000	44,9	150,7	0,30
5.500	50,0	222,7	0,22
6.000	51,7	244,0	0,21
Ranieri Next 330 Length 10,15 m Weight 5.280 kg (Max power 800 h 5 people – Calm la Propeller (16" x 21"	ake

COLOURS

These engines are available in Grand Prix White and Aquamarine Silver. Please contact your local Marine dealer for more information.



SPECIFICATIONS At a glance

BF350/300

ENGINE TYPE

5 LITRE 32 VALVE V8

DISPLACEMENT

4.952 CM3

WEIGHT

355 KG INCLUDING PROPELLER

HORSEPOWER Between 300-350 HP

RANGE BENEFITS

BUILT FOR SPEED

The V8 engine range offers the most formidable power yet amongst our outboard engines. At low speeds, BLAST[™] offers instant and powerful acceleration, then for the extra power at cruising speeds, initiate VTEC[™] to boost peak power to provide a positive surge of acceleration.

DESIGNED FOR EFFICIENCY

The new distinctive design – a slim, one-motion silhouette enveloped in Aquamarine Silver or Grand Prix White – adapts to various hull shapes and environments, while an improved gear case shape reduces underwater drag. Underneath built-in technology like ECOmo, Trim Support and an O2 sensor helps optimise fuel efficiency, without compromising engine performance.

TAILORED FOR EASE OF USE

Accompanying the new range is the all new V8 controller to help make the most of all the intuitive features. Experience smoother sailing with Cruise Control and its expanded adaptive speed range, then use the Automatic Tilt to set a default trim angle to avoid manually trimming the engine when docking and mooring.



SPECIFICATIONS

	BF350	BF300
Туре	4-Stroke, SOHC, 60° V8, 32 valves	4-Stroke, SOHC, 60° V8, 32 valves
Displacement (cc)	4.952	4.952
Bore x Stroke (mm)	89 × 99,5	89 × 99,5
Full Throttle RPM Range	5.000 - 6.000	5.000 - 6.000
Rated Power [kW (PS)]	257,4	220,7
Gear Ratio	1,79	1,79
Battery Charging Capacity (A)	70	70
Transom Height (mm)	XDU / XCDU: 638 UDU / UCDU: 765	XDU / XCDU: 638 UDU / UCDU: 765
Dry Weight (kg)	XDU / XCDU: 355* UDU / UCDU: 360*	XDU / XCDU: 355* UDU / UCDU: 360*
Engine Trim and Tilt	Power Trim & Tilt	Power Trim & Tilt
Length (mm)	1.121	1.121
Width (mm)	650	650
Height (mm)	2.145	2.145
Centre to Centre (mm)	742	742

	•	•
BLAST™ BLAST™	•	•
ECOmo ECOmo	•	•
Honda iST	•	•
Trim Support	• /	· /
Automatic Tilt	•	/ /• / /
Cruise Control	• /	•/ /
Control Mode	•	•/ /

BF250/BF225/BF200/BF175

V6. Engineering Evolved.

The very same manufacturing excellence that powers Honda motor racing, will power you to explore further, play harder and live freer than ever before. The advanced V6 range encapsulates the exhilaration of being out on the water. Enjoy the precision of rapid acceleration, the reassurance of intelligent fuel efficiency and, most importantly, the backing of years of proven Honda engineering.

[0]

SPECIFICATIONS AT A GLANCE BF250/225/200/175

ENGINE TYPE 6 Cylinders

DISPLACEMENT 3.583 CM³

WEIGHT From 272 kg

> HORSEPOWER Between 175-250 HP

RANGE BENEFITS

POWER TO TAKE YOU ANYWHERE

Whether you're working or cruising, you want a smooth and stress-free ride. The V6 range ensures exactly that, with innovative technologies including VTEC[™] control, BLAST[™] acceleration, and iST which enables precise electronic engine response.

BETTER FOR THE ENVIRONMENT

Enjoy impressive power output without an increase in fuel consumption. PGM-FI electronic fuel injection increases the air to fuel ratio when you accelerate, whilst ECOmo ensures the fuel efficiency continues when you reach optimal cruising speed.

CLEAN, SLEEK DESIGN

The V6 range was designed to be as sleek in appearance as it is on the water. The outer shell style echoes the precision engineering beneath the casing, leaving no doubt as to just what your boat can do at full throttle.

PERFECT FOR LARGER CRAFTS AND POWER SEEKERS

FUEL CONSUMPTION

	Engine speed (rpm)	Speed (knots)	Consumption (l/h)	MPL
	650	2,4	1,9	1,26
	1.000	3,8	3,3	1,15
	1.500	5,5	5,8	0,95
	2.000	6,9	7,4	0,93
	2.500	9,7	13,5	0,73
	3.000	15,0	20,0	0,75
	3.500	20,7	25,5	0,81
	4.000	25,3	35,0	0,72
	4.500	29,0	42,5	0,68
	5.000	33,2	53,9	0,62
	5.500	36,3	64,0	0,57
	6.000	40,0	80,5	0,50
	6.350 41,0		85,8	0,48
RANIERI SHADOW 24 - BF250 Length 7,15 m Weight 2.100 kg (as tested)			Max power 300 h 3 People - Calm se Propeller (15 1/2" x	ea

COLOURS

These engines are also available to order in Grand Prix White or Sporty White. Please speak to your local Marine dealer for more information.

H 250

Ho 225



Туре Displa Bore Full Th RPM F Rated Gear Batter Capac Trans Dry W Engir Lengt Width Heigh Cent VTE PLAST PGMecon

Fa

ŋ

IFICATIONS

	BF250*	BF225*	BF200*	BF175	
	OHC - 6 60° V6 VTEC	cylinders ∑™, 24 valves		cylinders 24 valves	
cement (cc)		3.5	583		
Stroke (mm)		89	x 96		
nrottle Range	5.300 - 6.300		5.000 - 6.000		
Power [kW (PS)]	183,9	165,5	147,1	128,7	
Ratio		2,0	00:1	$\langle \langle \rangle \rangle$	
y Charging ity (A)	$\langle \rangle \rangle$	e	50	() () ()	
om Height (mm)	$\langle \rangle \rangle \rangle$	L: 508 X*:	635 U*: 762	$\overline{) \setminus \langle \rangle}$	
eight (kg)	$\langle / / / \rangle$	L: 272 X / XC: :	287 U/UC: 291		
e Trim and Tilt	Power Trim & Tilt				
h (mm)	$\langle \rangle \rangle$	9	20		
(mm)	$\left \right \left \right \left \right $	6	60		
t (mm)		L: 1.788 X: 1.	.915 U: 2.042		
e to Centre (mm)		7	ווי		

FEATURES

	•	•		
BLAST™	•	•	•	•
Programmed Fuel Injection	·	•	•	
🛛 ECOmo	•	•	•	•
Honda iST	•/	•	· / •/ /	•
Electric Start	• /	- / - /		•
Power Trim and Tilt	•	(/•/)	/ /	•
Engine Protection and Security	•	•//		•
NMEA 2000	•	+ /	•	•
Counter Rotating Gearbox	//		•	
Through Hub Exhaust	/•//	/ +	•	•
er Power Air R Intake System	· /	/ /• /	•	•

THE POWER **TO PERFORM**

Designed with large inflatables and sports boats in mind, this range was inspired by the pure rush of feeling you get when you cut through the blue at top speed. With Intelligent Shift and Throttle (iST) technology, PGM-FI electronic fuel injection, and VTEC[™] to optimise engine performance, you get a small, finely tuned engine that promises a smooth and exhilarating ride for tenders, touring and anything in between.

SPECIFICATIONS AT A GLANCE

BF150/135/115 BF100/80

ENGINE TYPE 4 CYLINDERS 4 CYLINDERS

DISPLACEMENT

2.354 CM³

WEIGHT

HOND

0 .

FROM 218 KG FROM 165 KG

1.496 CM³

HORSEPOWER

BETWEEN 115-150 HP BETWEEN 80-100 HP

RANGE BENEFITS

VERSATILITY ON THE WATER

High performance means complete versatility. Honda's BF80-150 outboard offers the perfect balance for those who use a boat all day or for just a few hours of play.

RELIABILITY AND EFFICIENCY

Renowned for quality, reliability, and engineering that lasts, we make engines you can count on for work, rest, or play. Each model is packed with our clever fuel-efficient technology, making it as innovative as it is durable.

PERFECT FOR SPEEDBOATS AND ENTHUSIASTS

FUEL CONSUMPTION

Engine speed (rpm)	Speed (knots)	Consumption (l/h)		
650	2,0	0,9		
1.000	2,5	1,5		
1.500	4,3	3,3		
2.000	5,5	5,7		
2.500	7,1	8,1		
3.000	13,0	10,0		
3.500	17,0	12,3		
4.000	21,2	16,8		
4.500	25,5	20,1		
5.000	29,5	26,0		
5.500	33,0	32,4		
5.900	36,8	36,0		
Highfield H54 - BF100				

2 People - Calm sea

COLOURS

These engines are also available to order in Grand Prix White or Sporty White. Please speak to your local Marine dealer for more information.

150



VTEC'

PLAST

PGM-FI

ECOmo

ŋ

(

(f)

£

FR

୍ଚ୍ୟୁ

$\begin{array}{ c c c c c c } \hline \begin{tabular}{ c c c c } \hline \begin{tabular}{ c c c c c } \hline \begin{tabular}{ c c c c c c c } \hline \begin{tabular}{ c c c c c c c c c c c c c c c c c c c$						
16 valves VTEC" 16 valves (100 16 valves (80) nent (cc) 2.354 1.49 roke (mm) 87 x 99 73 x 89,4 tle 5.000 - 6.000 5.500 - 6.300 5.000 - 6. wer [kW (PS)] 110,3 99,3 84,6 73,6 58,8 o 2,14:1 2,33:1 harging (A) 40 35 1.49 Height (mm) L: 508 X: 635 L: 537 X: 664 ht (kg) L: 218 X: 221 LRTU: 166* LRTU: 167 LRTU: 172* XTRU: 172* tim and Tilt Power Trim & Tilt nm) 618 459 nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703		BF150	BF135	BF115	BF100	BF80
16 valves VTEC" 16 valves (100 16 valves (80) nent (cc) 2.354 1.49 roke (mm) 87 x 99 73 x 89,4 tle 5.000 - 6.000 5.500 - 6.300 5.000 - 6. wer [kW (PS)] 110,3 99,3 84,6 73,6 58,8 o 2,14:1 2,33:1 harging (A) 40 35 1.49 Height (mm) L: 508 X: 635 L: 537 X: 664 ht (kg) L: 218 X: 221 LRTU: 166* LRTU: 167 LRTU: 172* XTRU: 172* tim and Tilt Power Trim & Tilt nm) 618 459 nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703						
roke (mm) 87 x 99 73 x 89,4 tile ge 5.000 - 6.000 5.500 - 6.300 5.000 - 6. wer [kW (PS)] 110,3 99,3 84,6 73,6 58,8 o 2,14:1 2,33:1 harging (A) 40 35 Height (mm) L: 508 X: 635 L: 537 X: 664 ht (kg) L: 218 X: 221 LT: 537 X: 664 ht (kg) L: 218 X: 221 LT: 537 X: 664 ht (kg) L: 218 X: 221 LT: 537 X: 664 ht (kg) 742 m) 618 459 hm) L: 1.688 X: 1.815 L: 1.576 X: 1.703		16 valves			VTEC [™] 16 \	alves (100)
tile ge 5.000 - 6.000 5.500 - 6.300 5.000 - 6. wer [kW (PS)] 110,3 99,3 84,6 73,6 58,8 o 2,14:1 2,33:1 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3 10,3	nent (cc)		2.354	$\left(\right) \left(\right)$	1.4	96
ge 5.000 - 6.000 5.000 - 6.000 5.000 - 6.000 5.000 - 6.000 wer [kW (PS)] 110,3 99,3 84,6 73,6 58,8 o 2,14:1 2,331 harging (A) 40 35 Height (mm) L: 508 x: 635 L: 537 x: 664 ht (kg) L: 218 x: 221 LRTU: 166* xTRU: 172* LRTU: 166* xTRU: 172* rim and Tilt Power Trim & Tilt nm) 913 742 nm) 618 459 nm) L: 1.688 x: 1.815 L: 1.576 x: 1.703	roke (mm)		87 x 99		73 x	89,4
o 2,14:1 2,33:1 harging (A) 40 35 Height (mm) L: 508 X: 635 L: 537 X: 664 ht (kg) L: 218 X: 221 LRTU: 166* XTRU: 172* LRTU: 16* XTRU: 172* rim and Tilt Power Trim & Tilt 742 mn) 618 459 nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703		5.000 - 6.000			5.500 - 6.300	5.000 - 6.000
harging (A) 40 35 Height (mm) L: 508 X: 635 L: 537 X: 664 ht (kg) L: 218 X: 221 LRTU: 166* XTRU: 172* LRTU: 166* XTRU: 172* LRTU: 167* XTRU: 172* rim and Tilt Power Trim & Tilt 742 nm) 618 459 nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703	wer [kW (PS)]	110,3	99,3	84,6	73,6	58,8
(A) 40 35 Height (mm) L: 508 X: 635 L: 537 X: 664 ht (kg) L: 218 X: 221 LRTU: 166* XTRU: 172* LRTU: 172* LRTU: 172* rim and Tilt Power Trim & Tilt 742 mn) 618 459 nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703	0		2,14:1		2,3	33:1
L: 218 X: 221 LRTU: 166* XTRU: 172* LRTU: 16 rim and Tilt Power Trim & Tilt 742 nm) 618 459 nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703		40			3	55
nrt (kg) L: 2/8 X: 2/1 XTRU: 172* XTRU: 17 rim and Tilt Power Trim & Tilt 1 nm) 913 742 im) 618 459 nm) L: 1.688 X: 1.815	Height (mm)		L: 508 X: 635	()))	L: 537	X: 664
nm) 913 742 m) 618 459 nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703	ht (kg)	L: 218 X: 221				LRTU: 165* XTRU: 171*
Im) 618 459 nm) L:1.688 X:1.815 L:1.576 X:1.703	rim and Tilt	Power Trim &			rilt 🛛	
nm) L: 1.688 X: 1.815 L: 1.576 X: 1.703	nm)	913			74	42
	ım)	618			4	59
Contro (mm)	nm)	L:1.688 X:1.815			L: 1.576	X: 1.703
	Centre (mm)		$ / \rangle$	660	\mathbb{N}	

VTEC™	•			•	
BLAST™	•	•			
Programmed Fuel Injection	•	•	•	•	•
ECOmo	•) • /	· /	•	•
Honda iST	• /	•	/ •/ /		
Electric Start	•	+ /	/•/	_	^
Power Trim and Tilt	•	• / /	\ • / /	•	• /
Engine Protection and Security	•	•//	•	•	•
NMEA 2000	 •	//•//	•	0•	•
Counter Rotating Gearbox	[. .]	/ /• /			
Through Hub Exhaust		/ • /	•	•	•

COMPACT, LIGHT AND POWERFUL

With the power-to-weight ratio on our side, this light and nimble outboard range delivers thrilling acceleration and impressive fuel efficiency, so you can take on every wave and whim with ease. And you can rest assured that we've squeezed a lot of innovation into that compact shell, each technological advancement makes a day on the water as enjoyable as a freshly caught feast.

PERFECT FOR SMALLER BOATS REQUIRING MORE POWER

FUEL CONSUMPTION

1.000

1.500

2.000

2.500

3.000

3.500

4.000

4.500

5.000

5.500

6.000

6.200

Speed (knots)

2,2

3,0

3,6

5,4

5,8

6,8

9,8

15,7

19,1

22,0

24,5

27,2

28,1

Consumptior (l/h)

0,9

1,2

1,8 2,7

3,5

4,8 6,5

8,0

9,3

13,1

16,8

20,7

23,1

60

60 HONDA

ENGINE TYPE 3 CYLINDERS 3 CYLINDERS 12 VALVE 6 VALVE DISPLACEMENT 998 CM3 808 CM³ WEIGHT

BFP60/BF60

SPECIFICATIONS AT A GLANCE

FROM 110 KG FROM 96 KG HORSEPOWER

BF50/40

60 H P

BETWEEN 40-50 HP

RANGE BENEFITS

COMPACT DESIGN, **POWERFUL OUTPUT**

Designed with our unique BLAST[™] technology and PGM-FI, these three-cylinder engines offer greater performance at lower revs, so you can get to your optimum speed, and your favourite patch of blue, in no time at all.

EFFICIENT AND DURABLE

This durable Honda engine is equipped with ECOmo technology, to improve efficiency and lower running costs, and the option of Trolling Control. Ideal for fishing, this allows you to move smoothly through speed increments of just 50 rpm.

ROBUST SHELL

Innovative engineering housed in shimmering silver. Our patented double-seal process creates a slick aluminium shell that is anodised primed and painted before we finish with a clear top-coat of UV-protecting resin.





Туре Displa Bore Full Th RPM F Rated Gear Batter Capac Transo Dry W Engine Leng Width Heigh Cen BLAST PGM-F ECOm

୍ଚ୍ୟୁ

	BFP60	BF60	BF50	BF40
	OHC - 3 cy 12 valv		OHC - 3 0 6 va	
cement (cc)	998		80	08
Stroke (mm)	73 x 79,5		70 x 70	
nrottle Range	5.000 - 6.000		5.500 - 6.000	5.000 - 6.000
Power [kW (PS)]	44,	1	36,8	29,4
Ratio	2,33	2,07	2,0	28
y Charging ity (A)	22	17	17	
om Height (mm)	L: 531 X: 658	521	S: 416 / L: 521	
eight (kg)	LRTU: 119* XRTU: 125* 110*		SRTU: 96,0* LRTU: 98,0*	
e Trim and Tilt	Power T		rim & Tilt	
h (mm)	792	777	65	94
(mm)	417	()))))))))))))))))))	39	90
t (mm)	L: 1.453 X: 1.580	1.397	L: 1. X: 1.	
e to Centre (mm)	582		55	58

™ BLAST™	•	•	· ·	•
Programmed Fuel Injection	•	•	• /	•
e ECOmo	•	•	•	•
Multi- Function Tiller Handle**	• /	•	· /•/ /	•
Electric Start	•	•	 •	•
Power Trim and Tilt	•	•	/•/	•
Engine Protection and Security		•	-	•
NMEA 2000	•	• /	•	•
Through Hub Exhaust	//•//	• /	•0	•

THE STRONG, QUIET TYPE

Compact without the compromise. Our incredibly lightweight range of engines deliver impressive horsepower of 15 or 20 with a three-cylinder motor that promises a smoother, quieter ride across lake, river, or sea. Add some power to your dinghy, a kicker to your sailboat or some fun to your weekend. With clever foldaway handles, our ultra-portable range is the perfect pocket-sized power source.

HOND SPECIFICATIONS AT A GLANCE B F 3 O ENGINE TYPE 3 CYLINDERS 6 VALVE DIS 552

0 7

DISPLACEMENT	
552 CM ³	BETWEEN 350-222 CM ³
WEIGHT	
FROM 77,5 KG	FROM 42-46,5 KG
HORSEPOWER	

30 H P

BF20/15/10/8

2 CYLINDERS

4 VALVE

BETWEEN 8-20 HP

RANGE BENEFITS

THE PERFECT ALL-ROUNDER

Easily transported on land, powerful and intuitive in the water. With innovative additions such as remote control and the option of a nippy electric start, it's as easy to get up onto the plane as it is to get down to the shoreline. And, if you want to use your lightweight engine on a heavier boat, you can enhance capability with a power thrust propeller.

CONFIDENTLY QUIET

All Honda outboards come with the reassurance that our advanced technology means they start easily, operate efficiently, run quietly, and give you even less reason to be on dry land.

HIGHFIELD

PERFECT FOR SMALL BOATS AND RIBS

FUEL CONSUMPTION Consumption (l/h) Engine speed Speed (rpm) knots 4.000 11,7 3,8 4.500 15,0 4,3 5.000 18,0 5,1 5.600 20,3 6,8 Linder Sportsman 445 Basic - BF30 2 People - Calm sea



Туре

Displacen

Bore x Str

Full Throt RPM Ran

Rated Po

Gear Ratio

Battery (

Capacity

Transom

Dry Weigl

Engine Tr

Length (

Width (n Height (

	BF30	BF20	BF15	BF10	BF8			
	OHC 3 cylinders 6 valves			ylinders Ives				
nent (cc)	552	3!	50	2:	22			
oke (mm)	61 x 63	59 x	x 64	58 :	< 42			
tle ge	5.000 -	6.000	4.500 - 5.500	5.000 - 6.000	4.500 - 5.500			
wer [kW (PS)]	22,1	14,7	11,0	7,4	5,9			
0		2,08		2,33				
harging (A)	10			lectric) ecoil)				
Height (mm)	S: 431 / L: 552	$\langle \rangle \rangle \langle \rangle$		563 / X: 703 F15 and BF10)	$\overline{//}$			
ht (kg)	SRTU: 77,5* SHGU: 80,0* LRTU: 79,5* LHGU: 82,0*	SRU: 49,5* / LHU: 49,5* / LRU: 51,0* /	SHSU: 49,0* / SRTU: 57,0* / LHSU: 52,0* LRTU: 58,5* 51,0 (15)*	SHU: 42,0* / SRU: 46,0* LHU: 44,5* / LRU: 48,5* SHSU: 45,5* / LHSU: 48,0* XRUU: 52,5* (10)				
im and Tilt	Gas Assist Tilt Power Trim & Tilt		t - 5 stages er Tilt	Manual Tilt - 5 stages				
nm)	720 (Tiller) 640 (Remote)	650 (Tiller) / 6	540 (Remote)	610 (Tiller) / 600 (Remote)				
m)	375	3!	50	34	¥5			
nm)	S: 1.195 / L: 1.320		′ L: 1.240 30 (15)		′ L: 1.235 ′5 (10)			

Honda Programmed Ignition	•	•	•	•	•
Electric Start	•	•	/• /	/ •	•
Remote Control	• /	•		/•/	•
Power Trim and Tilt	•	Power Tilt only	Power Tilt only		
Through Hub Exhaust	•	•	/ + /	•	•
Engine Protection and Security	•	• / /	•	•	•

BF6/BF5/BF4/BF2.3

17

PORTABLE PERFORMANCE

Power so portable, you really can take it anywhere. Impromptu picnic? Last minute fishing trip? Unexpectedly sunny afternoon? Simply hitch up the boat trailer, load our compact and lightweight engine into the boot and go. Easy to move, easy to use and easily enough power for every spontaneous adventure.

PERFECT FOR SMALL BOATS AND RIBS OR USERS LOOKING FOR MAXIMUM PORTABILITY



RANGE BENEFITS LIGHT ENOUGH TO TAKE ANYWHERE

Whether you're forever seeking undiscovered pit stops or you just want to spend the weekend in a wetsuit. Our engines pack enough punch to take you places in a small boat, and, thanks to the ergonomic carry handle and folding tiller, they are then compact enough to be carried back to the car when the fun is over.

GIVES YOU CONFIDENCE ON THE WATER

When you're confident in your engine, you can cruise the river without a care. Along with the backing of Honda's worldrenowned reliability, you can also make the most of impressive fuel capacity ranging from 1,3 to 1,5 L giving you more than 60 minutes run time. Perfect for seeking out that little-known lunch spot.



(∰D



BF6/5/4 BF2.3 ENGINE TYPE

SPECIFICATIONS AT A GLANCE

DISPLACEMENT 127 CM³ 57 CM³

WEIGHT FROM 27 KG FROM 13 KG

HORSEPOWER Between 4-6 HP 2,3 HP



SPECIFICATIONS

	DEC		DEA	
	BF6	BF5	BF4	BF2.3
	ý.	A	F	
	OHV - 1 0 2 va			l cylinder alves
cement (cc)		127		57
Stroke (mm)		60 x 45		45 x 36
rottle ange	5.000 - 6.000	4.500	- 5.500	5.000 - 6.000
Power [kW (PS)]	4,4	3,7	2,9	1,7
atio		2,08		2,42
y Charging ty (A)	(specif	12V6A ic BF5 and BF6 n	nodels)	$\langle \rangle \langle \rangle$
m Height (mm)	$\langle \ \rangle \ \rangle$	S: 434 / L: 561		S: 418 / L: 571
eight (kg)	\leq	S: 27,0 / L: 27,5		SCHU: 13,5* LCHU: 14,0*
e Trim and Tilt	Ма	anual Tilt - 5 stag	les	Manual Tilt - 4 stages
n (mm)	()	524	UUU	410
(mm)		347	$\left(\right) \left(\right) \left(\right) $	280
: (mm)		S: 1.020 / L: 1.147	$\langle \rangle \rangle$	S: 945 / L: 1.100

FEATURES

Lightweight	•	•	•	•
Integrated Carrying Handle	•	•	•	•
Integrated Fuel Tank	·	·	• (•
Recoil Start	•	•	•	•
360° Steering				•
Throttle Tensioner	• /	•	•	•

hon **THE WATER IS WAITING**

Our stylish range of Honwave inflatables are light, portable and easy to use. Built from the highest grade marine PVC, they are tough, durable and capable of taking on the harshest of environments.

The option of three deck designs gives you the flexibility to choose from a compact slatted deck, which is easily stored, an extra-rugged aluminiumdeck, or our air V-floor, specifically created for stability and performance. All feature an extra wide tube diameter for a smooth ride and a smart new colour scheme; so wherever you go, the new Honwave will ensure you enjoy every adventure.



HONWAVE SLATTED-DECK INFLATABLES (SE)

(FROM 2 - 2,5 METRES)

Compact and ultra light, Honwave's slatted-deck inflatables are perfect for tender excursions or simply cruising for pleasure. With a larger buoyancy tube diameter, they ensure superior flotation and stability. Folding and storing can be accomplished by a single person in just minutes.

HONWAVE AIR V-FLOOR INFLATABLES (IE)

(FROM 2,4 - 3,8 METRES)

Light and fast, these inflatables are packed with comfort and performance features. Their deep-V hull design significantly optimises keel performance and ensures maximum stability.

HONWAVE ALUMINIUM DECK INFLATABLES (AE)

(FROM 2,5 - 4 METRES)

Honwave's aluminium-deck inflatables are ideal for just about any nautical activity. Rugged and ready to go, their extra-large buoyancy guarantees smooth and safe cruising every time. The floor slats are number coded for hassle-free assembly, and the smaller model can be stored in a single bag, so you can take them anywhere.



Туре	Overall Length (cm)	Overall Beam (cm)	Inner Length (cm)	Inner Beam (cm)	Tube Diameter (cm)	Packing Size (cm)	Net Weight (kg)	Max Engine Power (hp)	Passenger Capacity (Adult/Child)	Loaded Weight (kg)	Chambers	Floor	Category
LATTED	[S E]												
T20-SE3	202	144	121	61	40	107 x 60 x 32	27	4,3	2/-	250	3	Slatted	D
T25-SE3	250	156	153	68	43,5	112 x 60 x 34	34	6	3/-	440	3	Slatted	с
NFLATAE	LE (IE)												
T24-IE3	240	154	148	67	42,5	112 x 60 x 34	33	6	3/-	400	3 + Floor (2)	Air V-Floor	D
T27-IE3	267	153	177	67	42,5	112 x 65 x 38	34	8	3/1	664	3 + Floor (2)	Air V-Floor	С
T32-IE3	320	154	229	67	42,5	112 x 65 x 38	39	15	4/-	735	3 + Floor (2)	Air V-Floor	С
T38-IE3	376	170	262	80	44	122 x 72 x 43	48	20	5/1	950	3 + Floor (2)	Air V-Floor	с
	JM (AE)	_		\geq	\mathbb{N}								
T25-AE3	250	156	153	68	43,5	112 x 65 x 38	45	6	3/-	440	3 + Keel	Aluminium	С
T30-AE3	297	157	195,5	68	43	112 x 65 x 38	54	15	4/-	610	3 + Keel	Aluminium	С
T35-AE3	353	171	244	80	45	122 x 72 x 43	73	20	5/-	700	3 + Keel	Aluminium	С
T40-AE3	395	189	279	90	49	129 x 79 x 45	86	20	7/-	1.050	3 + Keel	Aluminium	с

Туре	Overall Length (cm)	Overall Beam (cm)	Inner Length (cm)	Inner Beam (cm)	Tube Diameter (cm)	Packing Size (cm)	Net Weight (kg)	Max Engine Power (hp)	Passenger Capacity (Adult/Child)	Loaded Weight (kg)	Chambers	Floor	Category
SLATTED	[SE]												
T20-SE3	202	144	121	61	40	107 x 60 x 32	27	4,3	2/-	250	3	Slatted	D
T25-SE3	250	156	153	68	43,5	112 x 60 x 34	34	6	3/-	440	3	Slatted	С
INFLATA	BLE (IE)												
T24-IE3	240	154	148	67	42,5	112 x 60 x 34	33	6	3/-	400	3 + Floor (2)	Air V-Floor	D
T27-IE3	267	153	177	67	42,5	112 x 65 x 38	34	8	3/1	664	3 + Floor (2)	Air V-Floor	С
T32-IE3	320	154	229	67	42,5	112 x 65 x 38	39	15	4/-	735	3 + Floor (2)	Air V-Floor	С
T38-IE3	376	170	262	80	44	122 x 72 x 43	48	20	5/1	950	3 + Floor (2)	Air V-Floor	с
ALUMINI	UM (AE)												
T25-AE3	250	156	153	68	43,5	112 x 65 x 38	45	6	3/-	440	3 + Keel	Aluminium	С
T30-AE3	297	157	195,5	68	43	112 x 65 x 38	54	15	4/-	610	3 + Keel	Aluminium	С
T35-AE3	353	171	244	80	45	122 x 72 x 43	73	20	5/-	700	3 + Keel	Aluminium	С
T40-AE3	395	189	279	90	49	129 x 79 x 45	86	20	7/-	1.050	3 + Keel	Aluminium	с

HONDA GENUINE **ACCESSORIES AND RIGGING COMPONENTS**

Honda genuine accessories are designed, made and tested to the same exacting standards as our legendary outboard engines. They are created to fit seamlessly with your existing Honda products without any hassle, allowing you to concentrate on the important things in life, enjoying the water.





HONDA IST INTELLIGENT SHIFT & THROTTLE

The iST command and control system is available on the BF115-350 models, providing superb control and plug-and-play installation. The system offers all of the features boaters are looking for including fast idle mode, trolling control, and engine speed and trim synchronisation (up to 4 engines). Mechanical controls are also available on the BF175 engine.

PROPELLER OPTIONS



3 BLADE ALUMINIUM PROPELLER







4 BLADE ALUMINIUM PROPELLER



4 BLADE STAINLESS STEEL PROPELLER

DISPLAYS

The 4,3 inch Multi-Function Display shows boat speed and fuel level (additional NMEA2000[®] sensors required) as well as any potential engine faults, for up to four Honda NMEA2000[®] compliant engines.



NMEA DISPLAY



Honda's ergonomically designed tiller handles and

HANDLING AND STEERING







MULTI-FUNCTION TILLER HANDLE (BF60A & BFP60A) (BF40D & BF50D)

SIDE MOUNT CONTROL BOX

CUSTOM FUNCTION BUTTONS

Our BF115-350 range features multiple rigging options for a customised on-the-water experience. Those fitted with iST (intelligent Shift & Throttle) offer a one-push button start.



PUSH START BUTTON



MULTIPLE CUSTOM FUNCTION SET-UPS

NMEA GAUGES

Utilising the NMEA2000[®] (engine-toelectronics data communication) network Honda's multifunction gauges output all manner of engine performance and management data to provide operators with accurate information from rpm and trim to fuel flow, trip speed/fuel consumption averages and much more.



MULTI-FUNCTION SPEEDOMETERS

IMMOBILISER

BF115-350 engines equipped with iST are available with an anti-theft immobiliser ignition system that requires a remote transponder key to start the engine.



HONDA iST (TWIN)



HONDA iST (SINGLE)



FLUSH MOUNT CONTROL BOX



TOP MOUNT CONTROL BOX (SINGLE)



TOP MOUNT CONTROL BOX (TWIN)



MULTI-FUNCTION TACHOMETERS



ANALOGUE FUEL GAUGE



ANALOGUE TACHOMETER

MARINE MULTI FUNCTION DISPLAY

Our all new 7" touchscreen Multi-Function Display allows you to effortlessly view all the data you need when out on the water. You can monitor, adapt, and adjust individual elements of your boat and engine, whilst easily navigating the waters as the interface centralises all the tools needed for travelling to your destination.

Navigation lets you to track your movement via a GPS compass and speed indicator. You can view Engine data including RPM, fuel level, engine temperature, trim and voltage, and an inbuilt Alarm will sound if there is an error with your engine, protecting it from serious faults and to ensure its longevity. The Audio screen acts as an interface for your onboard entertainment system* and lastly, Switches acts as a customisable digital control point so you can seamlessly control your electrical devices, with no

*Fusion Marine Entertainment system available to buy separately Marine Multi-Function Display





MARINE MONITOR APP*

Our Marine Monitor App gives you the ultimate connectivity. You can access live information such as engine, speed and battery data and boat owners can even track movement and receive an alert if their boat strays from a predefined geofenced area.

Trip data is stored automatically and can be viewed remotely via the smartphone app or web browser, making it easy for you to share your favourite routes with friends and family wherever you are.

Always connected and in control, whether you're in or out of the water.

*A unit is required to be fitted to the boat's NMEA system.



ADVENTURE ON WATER





PUDA SIM RERI IPSUMQUI CONASECT IBEATE OLENDI DOLU Aspi debis autas reicit, nonseque volorem nobit au

Puda sim reri ipsumqui consect ibeatem. Molendi dolupta tibeati aspidebis autas reicit, nonseque volorem nobit aut ut eum nisimporro optio. Ped ut quunt as simuscil et moluptat verum lam nobis doluptam ligenihic tem doluptatis volut andam abor sam res cum et que modionecae moluptatat ullabor ehenihicitat quiae estibus quis nonet alita si de volupta tiscium qui

Natio delignit auta inveribeatem quia comniatur asit, tes ipietur epudae Natio delignit auta inveribeatem quia comniatur asit, tes ipietur epudae maiosae rsperiate venditemo essinim explab id quatem fuga. Nemped eosa venis autas pari samus, sequis ad magnatios et ommolorem. Nequam aruntum qui cum ipiducid mos est, simusant hillorporro et velissitas et dolorpori dis et am doluptat.



WANT TO LEARN MORE?

ACTISORIES ROYOR

B HONWAVE

MEDIA GALLERY

Download our Honda Marine App to discover our full range of outboard engines and inflatables. Choose the engine you like, explore the technical spec, and take a 360 look around the exterior. We'll give you our recommendations on which model fits your needs and when you're ready to dive in, you can find your nearest dealer.



HOND



PTA TISBEATI UT



